

## PRODUCTS

### Silicone Sealant

- General use Silicone Sealant
- Structural Silicone Sealant
- Granite(marble) Sealant
- Waterproof Silicone Sealant
- IG Silicon Sealant
- Bathroom & Kitchen Sealant
- High Elasticity Sealant
- Fireproof Silicon Sealant
- Fire&weatherproof Sealant

### Polysulfide Sealant

- IG polysulfide sealant
- Polysulfide sealant in low temp
- Waterproof polysulfide sealant
- Fireproof polysulfide sealant

### Butyl Sealant

- Insulating Glass Butyl Sealant
- Butyl tape adhesive

### IG Material

- Spacer and plastic corner
- molecular sieve 3A

### Others

- Driveway sealant
- Organic protective agent
- Silicone sealant primer
- Epoxy stone sealant

## FS-210 hot melt Butyl Sealant

### INTRODUCTION

FS-210 is a kind of butyl sealant of single component, solvent free, non-fogging and permanently plasticity. The butyl sealant has good temperature adaptability, it keeps good plasticity, sealing quality and don't change hardness and surface quality in width extensive range.

The FS-210 butyl sealant has good adhesion to glass, aluminum, galvanized steel and stainless steel. There will construct a anti-humidity system when it work together with other sealant .

### APPLICATION

The FS-210 mainly used for the primary sealing of insulating glass.

### APPLICATION METHODS

The surface must be clean, dry and free of grease. FS-210 injected by butyl extruding machine (extruder) in IG production line. The preferred range of temperature is 110 to 150. We recommend operating environment temperature not lower than 10.



Items	Specifications
Color	Black, White, Transparent
Resistance to temperature	Continually used in the temperature range of 100~150 for 20hrs, it will not get hard or pulverous or loses adhesion. The highest temperature it can resist will be 180.
Resistance to UV	Comply GB/T 11944-2002
Dew point	Comply GB/T 11944-2002
Specific Gravity (g/m <sup>3</sup> )	1.15~1.20
Solid	100%
Operating Temperature Range (t)	-20~80

### PACKAGE

7 kg / barrel, 5kg/Barrel, 2kg/Barrel, four barrel per carton.  
We would like to make custom package as per customers' demand.

### TRANSPORTATION

FS-210 is non-dangerous and it could be delivered by different transportation methods such as truck, train, boat and plane, etc.

### STORAGE

Shelf life 24 months under temperature between -10~3.

