

## PRODUCTS

### Silicone Sealant

General use Silicone Sealant

Structural Silicone Sealant

Granite(marble) Sealant

Waterproof Silicone Sealant

IG Silicon Sealant

Bathroom & Kitchen Sealant

High Elasticity Sealant

Fireproof Silicon Sealant

Fire&weatherproof Sealant

### Polysulfide Sealant

IG polysulfide sealant

Polysulfide sealant in low temp

Waterproof polysulfide sealant

Fireproof polysulfide sealant

### Butyl Sealant

Insulating Glass Butyl Sealant

### Others

Driveway sealant

Organic protective agent

Silicone sealant primer

Epoxy stone sealant

## Silicone Sealant Primer

Sealan Tech's silicone sealant primer is a kind of solvent, it can easy cured and become a film when exposed in air for a short time.

### Operation guide:

1. Clean surface by a brush, use isopropanol, dimethylbenzene or butanone liquor will be better.
2. When the surface become dry and cleaniy, use clean brush or absorbent gauze paint Primer on the surface.
3. Sealant should be covered after primer cured fully.(Normally, 20minutes)

### Note:

1. The sealant must be covered within one hour after the primer painted.
2. Avoid contact skin in long time
3. Wash by plenty water if primer splashes into eyes.
4. Keep well ventilation in work place, because the primer is able to volatilize flammable gas.

### Package:

Metal Drum: 2 Liter Net vol: 1.5 Liter

### Storage:

Shelf-life: 12 months stored in cool(below 27<sup>o</sup>), dry and ventilated places.



Download pdf

Sealan Technologies Co., Ltd

Factory address: Xiangyang Industrial Zone, Hangzhou, 310022, Zhejiang province, China

Tel:86 571 8617 7866 Fax:86 571 5628 7663 E-mail: sales@silicone-sealant-china.com [XML Sitemap](#)